




| | | |
|---|----------------------|--|
| Model:E3-H | | Product Features: |
|  | | ◆ Easy installation and use, plug and play |
| | | ◆ View the video anytime and anywhere,support multiple platforms, terminals, networks |
| | | ◆ Clear and smooth video, intelligent transmission |
| | | ◆ Bank level security control and ensure privacy |
| | | ◆ Online firmware upgrade,update function and experience synchronously |
| | | ◆ Smart H.264 video compression algorithm, with lower video bit rates and saving more space when recording |
| | | ◆ Support two-way audio, telecommunication level of signal processing |
| | | ◆ Support Android /iOS system mobile devices, remote real-time monitoring |
| | | ◆ Motion detection, linkage snapshot/video recording, real-time App push notifications |
| | | ◆ Infrared night vision lighting(IR distance: 10 meters),24 hours day and night monitoring, IR-CUT switch |
| | | ◆ Support micro SD card (max 64 GB) storage, cloud box and cloud storage |
| | | ◆ Support QR code login |
| | | ◆ Support ditial zoom |
| ◆ Support 2.4G WIFI(IEEE802.11b/g/n) | | |
| ◆ Support P/T/Z remotely (Horizontal:350°& Vertical:100°) | | |
| Specifications | | 720P |
| Main CPU | | ARM |
| Image Sensor | Sensor | 1/2.9" CMOS |
| | Lens | f: 3.6mm, 720P |
| | Visual angle | H:80°; V:45°; D:92° |
| | Minimum illumination | 0.01Lux |
| Audio | Input/output | Built-in microphone (-36dB) and speaker (8Ω/1W), support two-way audio |
| | Audio compression | AAC |
| Video | Video compression | H.264 |
| | Lighting frequency | 50Hz, 60Hz |
| | Image frame rate | Max 30fps |
| | Display resolution | 720p |
| | Image adjustment | Brightness, Contrast, Saturation, Sharpness |
| | White balance, BLC | Automatically |
| Internet | Night vision | 6 dot matrix infrared lights, IR distance: 8 meters |
| | Wireless networks | 2.4G WIFI(IEEE802.11b/g/n),Built in PCB board 2DB antenna |
| | Ethernet | 10/100Mbps |
| | Protocols | TCP/IP、UDP/IP、HTTP、DHCP、RTMP、MUTP |
| Alarm | IP address | Static IP address and dynamic IP address |
| | Alarm detection | Motion detection |
| Record | Alarm linkage | Snapshot, audio/video record |
| | Alarm notification | Real-time App push notifications |
| | Video storage | Micro SD card (max 64GB) local storage, cloud box and cloud storage |
| Pan&Tilt | Record type | Continuous recording, motion detection recording... |
| | Record mode | Normal mode (4 days video could be recorded with 32GB SD card); Superior mode (10 days video could be recorded with 32GB SD card); Advanced mode (15 days video could be recorded with 32GB SD card) |
| Interface | Pan&Tilt | Horizontal:350°& Vertical:100° |
| | Power | DC 5V/1.2A Micro USB Interface (European,UK,USA type for option) power consumption < 8W |
| | Buttons | A RESET button |
| Others | Network interface | RJ45 |
| | Adjustable lens | No |
| Environment | Work temperature | -10° ~ 55°C (14°F ~ 131°F) |
| | Work humidity | 10% ~ 80% (No condensation) |
| | Storage temperature | -10°C ~ 60° (14°F ~ 140°F) |
| | Storage humidity | 0% ~ 90%(No condensation) |
| Color | Color | White / Black |
| Specifications | Size(L*W*H) | 85(L)X85(W)x120(H)mm |
| | Weight | 267g (not include rack) |
| Certification | Certificate | RoHS,CE,FCC,NCC |